

600 CAMEL X-CNC-2000 (version 3)

It is a highly efficient automatic hydraulically controlled band-saw with multiple material feed.

An unique construction of the band saw machine with three pulleys for leading of the blade. With the blade that is 10 grades sloped against the level guarantee high-efficiency of cutting. Thanks to this solution is the machine suitable for well cutting of L,H profiles as well as all types of pipes.

The machine is designed for vertical cuts.

It is suitable for serial production in industrial premises. Thanks to its robust construction enables to cut wide range of materials including stainless and tool steels, nonferrous metals both profiles and full materials.

Control system:

- Machine is equipped with programmable PLC SIEMENS SIMATIC S7-1200. Drive of band blade, movement of arm and movement of feeder are completely controlled and drive by SIEMENS technology.
- The coloured touch screen HMI SIEMENS TP 700 COMFORT enables easy communication with an operator. It shows working conditions (blade speed, moving to the cut, cutting parameters etc.)
- The machine enables to work with two modes:
 - SEMIAUTOMATIC CYCLE: The machine cuts the material immediately in a semiautomatic mode. The operator uses the feeder of the machine for the manipulation with the material and for the exact feed of the material into the cutting zone. The movement of the feeder is realized by manual buttons or by GTO function. After starting GTO function the operator sets the position of the feeder, presses START GTO button and feeder goes to the set position.
 - AUTOMATIC CYCLE: the feeder feeds the material according to the set programm. The operator sets the cutting programm, machine realizes these programmes, it is possible to make thousand different programmes. The part of one programm is a complete setting of the cut: blade speed, feed speed, setting of an automatic regulation, setting of the height of the bar to be cut, setting of the length of the bar, angles values and number of pieces. The length and number of pieces it is possible to set in 20 lines, the machine feeds differently set lengths automatically.
- Regulation of cutting feed is realized by controlled system by the servo-motor and throttle valve of hydraulic. Then is reached very precise cutting feed. Operator will input into program required cutting feed (mm/min) and bandsaw this cutting feed precisely set.
- Two basic regimes of automatic system regulation (ASR): ARP a RZP.
 - RZP = Zone regulation. System enable to cut material in 5 zones, because of setting optional cutting feed and blade speed according on blade position. Operator can choose from 2 strategy settings: DEFENSIVE setting is appropriate for cutting very hard materials with use of carbide band blade. Cutting feed is in beginning and in the end reduced. OFFENSIVE settings supports executive cutting logs. Cutting feed and band speed are in the beginning and in the end of cut increased. It's about similar principle as ARP mode. Advantage is regulation of blade speed.
 - ARP = System of the automatic regulation of the cutting feed rate depending on the cutting resistance of the material or blunting the blade. System offers two basic modes of ARP: BIMETAL and CARBIDE.
 - BIMETAL mode is suitable for optimization of the cutting feed when cutting profiles by bimetal blades. The cutting feed is higher if the blade cuts sides of the profile. As the blade reaches the full material, the system reduces the cutting feed automatically so that teeth gap of the blade would not be filled.
 - CARBIDE mode is suitable for cutting of full bars. If the blade is old (blunt), loaded is the cutting feed reduced Reaction time is slower than in mode BIMETAL.
- The control panel is equipped with mechanical buttons and digital display of the machine control system. Mechanical buttons controls basic saw movements (arm, vice, feeder) and cutting cycle start. The safety button is present on the panel aswell. All buttons are highly resistant in anti-vandal version.
- Safety module with autodiagnosics.

Construction:

- The machine is constructionally designed in that way, so that it corresponds to extreme exertions in productive conditions. A robust construction of machine includes vice allows to take advantage of bimetal blades maximally.
- The arm of machine with columns situated as near the clamping vice as possible minimizes vibrations and enables max. cutting performance.
- The arm of the machine is robust, heavy weldment and it is designed so that a toughness and a precision of cut was ensured.
- The arm moves along two columns using a four row linear leading with a high loading capacity. Arm movement using two hydraulic cylinders.
- 3 pulleys from cast iron are used.
- The arm uses incremental sensor for evaluation of current position above material. Upper working position of the arm is possible to set in control system.
- Down working position is set with adjustable mechanical stop and microswitch. Down working position of the arm is also possible to set in the saw control system. After reaching bottom H1769:1781 working position the arm stops in the position set in the system.
- Main vice is massive steel weldment. Its jaws are iron casting.
- Hydraulic, long stroke main vice. Jaws enable well clamping of material.
- Jaws of the main vice move in steel leading using hydraulic cylinder. One jaw is longstroke (the movement by longstroke hydraulic cylinder), one is fixed.
- Regulation valves for setting a vice pressure in hydraulic system.

- Very firm feeder with feeding 2000 mm is moving along 4-rails linears. The feeder movement is provided by bevel gear box, cogwheel and geared rack.
- Transporter is driven by electric engine with mechanical brake and frequency convertor.
- Indication of actual position by incremental sensor, which reads operating speed of gearbox output shaft.
- Indication of material in the feeder: optic sensor - it notices that there is a material in the feeder. If there is no material in the feeder, the signal reflects on the glass that is situated on movable jaw and it goes back to the sensor. The machine stops feeding and waits for another bar.
- The roller conveyer goes through the whole machine and supports the material in all its length. The roller conveyer of the feeder : bearings houses of the rollers are mounted into the basement – big robustness and precision.
- The feeder clamping vice is a robust steel weldment. Jaws ensure safe clamping of the material.
- Jaws of the feeding vice move along two-rails linears using hydric cylinder. One jaw is long stroke (the movement by longstroke hydraulic cylinder). Second jaw is short stroke (utilization during bar feeding: not jaw wearing out, not slipping of material). Short stroke jaw is suitable for feeding of deformed material.
- Cutting zone is opened from side of the feeder device automatically, extends the blade lifetime when arm is moving to top position.

Basic equipment of machine:

- The blade leading in guides with hardmetal plates and leading bearings and along cast iron pulleys.
- The blade is 10 grades sloped regarding the level of the vice => higher performance when cutting, profiles, longer bladeflife, higher performance when cutting full materials.
- There is a guide situated on the firm beam on the drive side. On the tightening side there is the guide situated on the moving beam.
- The guide beams of moving band guide is adjustable in whole working range. Manual adjustment and fixing of the guide beams.
- Hydraulic tightening of band.
- Automatic indication of blade tension.
- A cleaning brush is driven by an electroengine and ensures perfect cleaning of a blade.
- Drive of machine is solved by worm gear box with maintenanceless oil filling. Three-phases electromotor with double winding, with a frequency converter for a fluent regulation of the blade speed from 20 to 100 m/min. Sturdy flange with shaft. Termoprotection of engine.
- The cooling system for emulsion, leaded to the guides of the blade and by LocLine system directly to the cut groove.
- Massive base with a tank for chips. Base is designed for manipulation manipulation with machine by pallet truck and also by any hight lift truck or by crane.
- Indication of blade tightening and opening of the cover.
- Controlling 24 V.
- Machine is equipped with hydraulic system which controles all functions of that maschine. It pushes the arm to cut, pulls up the arm, opens and closes vices, moving of feeder.
- ven by electric engine with mechanical brake and frequency convertor.
- Indication of actual position by incremental sensor, which reads operating speed of gearbox output shaft.
- Indication of material in the feeder: optic sensor - it notices that there is a material in the feeder. If there is no material in the feeder, the signal reflects on the glass that is situated on movable jaw and it goes back to the sensor. The machine stops feeding and waits for another bar.
- The roller conveyer goes through the whole machine and supports the material in all its length. The roller conveyer of the feeder : bearings houses of the rollers are mounted into the basement – big robustness and precision.
- The feeder clamping vice is a robust steel weldment. Jaws ensure safe clamping of the material.
- Jaws of the feeding vice move along two-rails linears using hydric cylinder. One jaw is long stroke (the movement by longstroke hydraulic cylinder). Second jaw is short stroke (utilization during bar feeding: not jaw wearing out, not slipping of material). Short stroke jaw is suitable for feeding of deformed material.
- Cutting zone is opened from side of the feeder device automatically, extends the blade lifetime when arm is moving to top position.







Basic accessories of machine:

- Lighting of workink space.
- Band saw blade.
- Set of spanners for common service.
- Manual instructions in eletronic form (CD).

Operating cycle:

After starting the machine, vices clamp after starting the machine, the machine makes the cut by a set speed, the cutting zone in the down position of the arm is released - the longstroke jaw of the firm vice open, the feeder moves the material to the firm vice, the arm lifts up to the set upper position. The material is moved by the feeder – periodic regime (feeder moves between zero position and the position of the set lenght of feed) or consecutive regime (feeder moves to the limit position and clamps the material and feed it to the cut consecutively). The main vice clamps the material, the vice of the feeder is still closed and the whole procedure repeats. The operator only loads the material and removes the cut material. It is possible to regulate the cutting speed of the arm and the blade speed during cutting.

cutting parameters

		 0°		
	D [mm]	600	x	
	D [mm]	400*	x	
	axb [mm]	600x510	600x415	

* Recommended values. Recommendations of band blade producers are to be followed when choosing to cut full material, their dimensions are limited by available size of the teeth for the specific type of the band.

° Cutting of the bundle without upper vice HP. HP = accessory for additional price. The cutting parameters are limited when using.

performance parameters

drive of the blade	kW	4,0
drive of the hydraulic agregate	kW	1,8
pump of the cooling emulsion	kW	0,12
electroengine of the cleaning of the blade	kW	0,12
electroengine of the drive of the worm chip extractor	kW	0,18
Chip transporter	kW	2,2
Control circuit	kW	0,5
total input	kW	9
cutting speed – fluently set	m/min	20-100
diameter of the blade	mm	6230x41x1,3
electric connection		3x400V, 50 Hz, TN-S

control

feed of the Frame to the cut	hydraulically
feed of the material	hydraulically
clamping of material	hydraulically
bend tension	Manually/ hydraulically -accessories
cleaning of the blade	A cleaning brush is driven by an electroengine

Parameters

length	width	Height		height of the table	weight
[L]	[B]	[Hmax]	[Hmin]	[V]	(kg)
3020	4000	2600	2300	800	3630

